

View Online at <https://aerobasegroup.com/nsn/5320-01-522-8269>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.802 inches and 0.822 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.0791 inches and 0.0801 inches

Head Major Diameter:

Between 0.2564 inches and 0.2612 inches

Lubrication:

Cetyl alcohol

End Application:

1520-01-355-8250

Grip Length:

0.5625 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160 pounds per square inch

Thread Size:

0.164 inches

Shear Strength:

4010 double pounds per square inch

Countersink Angle:

100.0 degrees

Criticality Code Justification:

Aazg and aatb and anee

Product Name:

Pin-rivet, threaded, 100 flush shear head, hex point drive, alloy steel

Material:

Steel comp 4140 or steel comp 4130 or steel comp 8740

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type ii.Class 2 federal specification single treatment response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0