

View Online at <https://aerobasegroup.com/nsn/5320-01-522-8356>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 2.065 inches and 2.085 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.079 inches and 0.081 inches

Shank Diameter:

Between 0.189 inches and 0.190 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.377 inches and 0.381 inches

End Application:

1520-01-082-0686

Grip Length:

Between 1.745 inches and 1.755 inches

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.190 inches

Countersink Angle:

100.0 degrees

Special Features:

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6758 military specification 3rd material response

Material:

Steel comp 4140 or steel comp 8740 or steel comp 4130

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2. Cl 3 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5626 spec.