

View Online at <https://aerobasegroup.com/nsn/5320-01-523-0333>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Head Style:**

Err-090

**Head Height:**

Between 0.178 inches and 0.188 inches

**Width Between Flats:**

Between 0.269 inches and 0.289 inches

**Shank Diameter:**

Between 0.499 inches and 0.500 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.717 inches and 0.752 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**End Application:**

A-10

**Grip Length:**

Between 1.995 inches and 2.005 inches

**Thread Qty Per Inch (tpi):**

20

**Thread Size:**

0.500 inches

**Shear Strength:**

37300 double pounds per square inch

**Product Name:**

Hy-lok

**Material:**

Steel comp 4340

**Material Specification:**

Ams6415 assn standard all material responses

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type ii. Class 2 federal specification all treatment responses

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0