## NSN 5320-01-523-2467

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-523-2467 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 3.965 inches and 3.990 inches **Head Style:** Flush countersunk **Shank Diameter:** 0.7929 inches **Shank Style:** Err-090 **Head Major Diameter:** Between 1.077 inches and 1.162 inches **Tip Diameter:** Between 0.6163 inches and 0.6230 inches **End Application:** B1-b acft **Grip Length:** Between 3.240 inches and 3.255 inches Thready Qty Per Inch (tpi): 18 **Thread Size:** 0.6250 inches **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Special Features:** 125 ksi min. Shear; 220 ksi min. Tensile; lubrication dry f Material: Steel comp xm-13 **Material Specification:** Aastm 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

Unit Of Measure:

N/a

## NSN 5320-01-523-2467

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0