

View Online at <https://aerobasegroup.com/nsn/5320-01-523-3585>

Thread Class:

3a

Thread Direction:

Right-hand

Head Style:

Countersunk w/reverse chamfer

Head Height:

Between 0.064 inches and 0.074 inches

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.1885 inches and 0.1895 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.357 inches and 0.377 inches

Collar Outside Diameter:

Between 0.303 inches and 0.307 inches

Collarheight:

Between 0.437 inches and 0.457 inches

Collar Inside Diameter:

Between 0.192 inches and 0.200 inches

Grip Length:

0.437 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.190 inches

Countersink Angle:

Between 90.0 degrees and 100.0 degrees

Collar Style:

Threaded break off type

Material:

Steel comp 4340 body or steel comp 4140 body or steel comp 8740 body

Material Specification:

Qq-a-250/4 federal specification single material response washer or qq-a-250/5 federal specification single material response washer

Surface Treatment:

Cadmium collar

Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response body

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.