

View Online at <https://aerobasegroup.com/nsn/5320-01-523-3590>

Thread Class:

3a

Thread Direction:

Right-hand

Head Style:

Countersunk w/reverse chamfer

Head Height:

Between 0.055 inches and 0.065 inches

Width Between Flats:

Between 0.0791 inches and 0.0801 inches

Shank Diameter:

Between 0.1625 inches and 0.1635 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.306 inches and 0.322 inches

Collar Outside Diameter:

Between 0.288 inches and 0.292 inches

Collarheight:

Between 0.427 inches and 0.447 inches

Collar Inside Diameter:

Between 0.166 inches and 0.173 inches

Grip Length:

0.375 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.164 inches

Countersink Angle:

Between 90.0 degrees and 100.0 degrees

Collar Style:

Threaded break off type

Material:

Steel comp 4340 body or steel comp 4140 body or steel comp 8740 body

Material Specification:

Qq-a-430 federal specification single material response collar or qq-a-225/6 federal specification single material response collar

Surface Treatment:

Cadmium body and chromate body

Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response body

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6094 spec.