## NSN 5320-01-523-6801

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-523-6801 **Thread Class:** За **Thread Direction:** Right-hand **Head Style:** Err-090 **Head Height:** Between 0.130 inches and 0.140 inches Width Between Flats: Between 0.197 inches and 0.217 inches **Shank Diameter:** Between 0.374 inches and 0.375 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.530 inches and 0.565 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **End Application:** A-10 **Grip Length:** Between 2.058 inches and 2.068 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.375 inches **Shear Strength:** 21000 double pounds per square inch **Product Name:** Hy-lok Material: Steel comp 4340 or steel comp 8740 **Material Specification:** Ams6415 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Ams-qq-p-416, type ii. Class 2 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

## NSN 5320-01-523-6801

Pin-rivet - Page 2 of 2



|    | • • |             |    |     |      |
|----|-----|-------------|----|-----|------|
| In | 18  | <i>(</i> )+ | МА | 261 | ıre: |
|    |     |             |    |     |      |

--

Demilitarization:

No

Fiig:

A528u0