

View Online at <https://aerobasegroup.com/nsn/5320-01-524-6003>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

1.482 inches

Head Style:

Err-090

Head Height:

Between 0.078 inches and 0.088 inches

Width Between Flats:

Between 0.1582 inches and 0.1617 inches

Shank Diameter:

Between 0.373 inches and 0.374 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.565 inches and 0.600 inches

Lubrication:

Cetyl alcohol

Grip Length:

0.937 inches

Thready Qty Per Inch (tpi):

24

Thread Size:

0.375 inches

Material:

Steel comp 4130 or steel comp 4140 or steel comp 8740 or steel comp 4340

Material Specification:

Mil-s-6758 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 4th material response or ams 6415 assn standard 5th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, tyii, cl2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6758 spec.