NSN 5320-01-524-6005

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-524-6005 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 1.770 inches **Head Style:** Err-090 **Head Height:** Between 0.056 inches and 0.069 inches Width Between Flats: Between 0.094 inches and 0.096 inches **Shank Diameter:** Between 0.248 inches and 0.249 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.387 inches and 0.412 inches Lubrication: Cetyl alcohol **Grip Length:** 1.375 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches Material: Steel comp 4130 or steel comp 4140 or steel comp 8740 or steel comp 4340 **Material Specification:** Mil-s-6758 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 4th material response or ams 6415 assn standard 5th material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, tyii, cl2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5320-01-524-6005

Pin-rivet - Page 2 of 2



Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6758 spec.