
NSN 5320-01-524-6012

Pin-rivet - Page 1 of 2





Thread Class:

3a

Fastener Length:

1.310 inches

Head Style:

Err-090

Head Height:

Between 0.103 inches and 0.115 inches

Hole Diameter:

0.279 inches

Shoulder Diameter:

0.4995 inches

Shoulder Length:

0.625 inches

Shank Diameter:

Between 0.488 inches and 0.493 inches

Shank Style:

Err-090

Head Major Diameter:

Between 0.735 inches and 0.770 inches

Hole Depth:

0.240 inches

Lubrication:

Cetyl alcohol

Thready Qty Per Inch (tpi):

20

Thread Size:

0.500 inches

Material:

Steel comp 4130 or steel comp 4140 or steel comp 8740 or steel comp 4340

Material Specification:

Mil-s-6758 military specification single material response or mil-s-5626 military specification single material response or mil-s-6049 military specification single material response or ams 6415 assn standard single material response or ams 6484 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

NSN 5320-01-524-6012

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6758 spec.

