## NSN 5320-01-524-6012



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-524-6012 **Thread Class:** За Fastener Length: 1.310 inches **Head Style:** Err-090 **Head Height:** Between 0.103 inches and 0.115 inches **Hole Diameter:** 0.279 inches **Shoulder Diameter:** 0.4995 inches **Shoulder Length:** 0.625 inches **Shank Diameter:** Between 0.488 inches and 0.493 inches **Shank Style:** Err-090 **Head Major Diameter:** Between 0.735 inches and 0.770 inches **Hole Depth:** 0.240 inches Lubrication: Cetyl alcohol Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.500 inches Material: Steel comp 4130 or steel comp 4140 or steel comp 8740 or steel comp 4340 **Material Specification:** Mil-s-6758 military specification single material response or mil-s-5626 military specification single material response or mil-s-6049 military specification single material response or ams 6415 assn standard single material response or ams 6484 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type ii, class 2 federal specification single treatment response **Thread Series Designator:** Unjf

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 5320-01-524-6012

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6758 spec.