## NSN 5320-01-524-7799

Pin-rivet - Page 1 of 2

**Thread Class:** 

Right-hand

**Head Style:** 

**Thread Direction:** 

Fastener Length:

Flush countersunk

Between 1.122 inches and 1.142 inches

За



View Online at https://aerobasegroup.com/nsn/5320-01-524-7799

Head Height:
0.135 inches
Width Between Flats:
Between 0.1270 inches and 0.1295 inches
Shank Diameter:
Between 0.3115 inches and 0.3120 inches
Head Major Diameter:
0.6335 inches
End Application:
F22
Grip Length:
Between 0.683 inches and 0.693 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
12300 pounds per square inch
Thread Size:
0.3125 inches
Shear Strength:
19160 double pounds per square inch
Countersink Angle:
Between 99.30 degrees and 100.30 degrees
Special Features:
B"indicates cross lock features
Material:
Nickel alloy 718
Material Specification:
Ams5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal standard single treatment response
Thread Series Designator:
Unjf

## NSN 5320-01-524-7799

Pin-rivet - Page 2 of 2



	<b>L</b> -	11		ife	_
3	ne	п	_	пе	Ξ

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0