NSN 5320-01-525-0985

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-525-0985 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.965 inches and 0.987 inches **Head Style:** Err-090 **Head Height:** Between 0.080 inches and 0.090 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Head Major Diameter:** Between 0.415 inches and 0.440 inches **End Application:** F22 **Grip Length:** Between 0.620 inches and 0.630 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 5820 pounds per square inch **Thread Size:** 0.2500 inches **Shear Strength:** 9300 double pounds per square inch **Special Features:** S"indicates spline lock recess Material: Titanium alloy **Material Specification:** Ams4928 assn standard single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Ams2486 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5320-01-525-0985

Pin-rivet - Page 2 of 2



| | Of | | | |
|--|----|--|--|--|

--

Demilitarization:

No

Fiig:

A528u0