NSN 5320-01-525-0985

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-525-0985



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.965 inches and 0.987 inches

Head Style:

Err-090

Head Height:

Between 0.080 inches and 0.090 inches

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2490 inches and 0.2495 inches

Head Major Diameter:

Between 0.415 inches and 0.440 inches

End Application:

F22

Grip Length:

Between 0.620 inches and 0.630 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

5820 pounds per square inch

Thread Size:

0.2500 inches

Shear Strength:

9300 double pounds per square inch

Special Features:

S"indicates spline lock recess

Material:

Titanium alloy

Material Specification:

Ams4928 assn standard single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Ams2486 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

NSN 5320-01-525-0985

Pin-rivet - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

