NSN 5320-01-525-2981

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-525-2981 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.340 inches and 1.360 inches **Head Style:** Err-090 **Head Height:** Between 0.059 inches and 0.069 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.387 inches and 0.412 inches **End Application:** F22 **Grip Length:** Between 0.995 inches and 1.005 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 4300 pounds per square inch **Thread Size:** 0.2500 inches **Shear Strength:** 9300 double pounds per square inch Material: Titanium alloy **Material Specification:** Ams 4928 assn standard single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Ams 2846 assn standard single treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

NSN 5320-01-525-2981

Pin-rivet - Page 2 of 2



| ш | ın | 10 | <i>(</i>)+ | Measure: | |
|---|----|----|-------------|----------|--|
| | | | | | |

--

Demilitarization:

No

Fiig:

A528u0