NSN 5320-01-525-4639

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Head Style:

Thread Direction:

Fastener Length:

Between 0.400 inches and 0.420 inches

За



View Online at https://aerobasegroup.com/nsn/5320-01-525-4639

Err-090
Head Height:
Between 0.037 inches and 0.047 inches
Width Between Flats:
Between 0.0791 inches and 0.0806 inches
Shank Diameter:
Between 0.1630 inches and 0.1635 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.242 inches and 0.262 inches
End Application:
F22
Grip Length:
0.1250 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
1940 pounds per square inch
Thread Size:
0.1640 inches
Shear Strength:
4010 double pounds per square inch
Special Features:
S"indicates spline lock recess
Material:
Titanium alloy
Material Specification:
Ams 4928 assn standard single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Ams 2846 assn standard single treatment response
Thread Series Designator:
Unjc

NSN 5320-01-525-4639

Pin-rivet - Page 2 of 2



She	lf	Life:	
Oile	••	LIIV.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0