NSN 5320-01-525-4983

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Head Style:

Thread Direction:

Fastener Length:

Between 0.588 inches and 0.608 inches

За



View Online at https://aerobasegroup.com/nsn/5320-01-525-4983

riedd Otyle.	
Err-090	
Head Height:	
Between 0.055 inches and 0.060 inches	
Width Between Flats:	
Between 0.0791 inches and 0.0806 inches	
Shank Diameter:	
Between 0.1630 inches and 0.1635 inches	
Shank Style:	
Pin-rivet, straight, threaded	
Head Major Diameter:	
Between 0.306 inches and 0.322 inches	
End Application:	
F22	
Grip Length:	
0.3125 inches	
Thready Qty Per Inch (tpi):	
32	
Min. Tensile Strength (psi):	
2180 pounds per square inch	
Thread Size:	
0.1640 inches	
Shear Strength:	
4010 double pounds per square inch	
Special Features:	
S"indicates spline lock recess	
Material:	
Titanium alloy	
Material Specification:	
Ams 4928 assn standard single material response	
Surface Treatment:	
Anodize	
Surface Treatment Specification:	
Ams 2486 assn standard single treatment response	
Thread Series Designator:	
Unjc	

NSN 5320-01-525-4983

Pin-rivet - Page 2 of 2



Shelf Life:	She	lf	Life:
-------------	-----	----	-------

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0