

View Online at <https://aerobasegroup.com/nsn/5320-01-525-5757>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.545 inches and 0.565 inches

Head Style:

Flush countersunk

Head Height:

0.046 inches

Width Between Flats:

Between 0.0791 inches and 0.0805 inches

Shank Diameter:

Between 0.1890 inches and 0.1895 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

0.266 inches

End Application:

F22

Grip Length:

Between 0.245 inches and 0.255 inches

Thread Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

2000 pounds per square inch

Thread Size:

0.1900 inches

Shear Strength:

5380 double pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Special Features:

S"indicates spline lock recess

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response

Surface Treatment:

Phosphate

Surface Treatment Specification:

Ams 2486 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0