NSN 5320-01-525-6328

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-525-6328

Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 0.488 inches and 0.508 inches
Head Style:
Flush countersunk
Width Between Flats:
0.100 inches
Shank Diameter:
Between 0.1630 inches and 0.1635 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
0.237 inches
Lubrication:
Cetyl alcohol
End Application:
Rq-4-a
Grip Length:
Between 0.307 inches and 0.317 inches
Thready Qty Per Inch (tpi):
32
Thread Size:
0.164 inches
Shear Strength:
4010 double pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Product Name:
Pin, flush, eddie
Special Features:
Spline-lok recess
Material:
Titanium alloy uns r56400
Material Specification:
Ams4928 assn standard single material response or ams4967 assn standard single material response
Thread Series Designator:
Unjc
Shelf Life:
N/a

NSN 5320-01-525-6328

Pin-rivet - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A528u0