NSN 5320-01-525-6334

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-525-6334 **Thread Class:** За **Thread Direction:** Right-hand **Head Style:** Flush countersunk Width Between Flats: 0.100 inches **Shank Diameter:** Between 0.1630 inches and 0.1635 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.237 inches Lubrication: Cetyl alcohol **End Application:** Rq-4a **Grip Length:** Between 0.370 inches and 0.380 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.164 inches **Shear Strength:** 4010 double pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Pin, eddie, flush **Special Features:** Spline-lok recess Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Thread Series Designator:** Unjc Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-525-6334

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0