# NSN 5320-01-525-6349

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-525-6349



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

### Fastener Length:

Between 0.712 inches and 0.732 inches

#### Head Style:

Flush countersunk

#### Width Between Flats:

0.100 inches

#### Shank Diameter:

Between 0.1630 inches and 0.1635 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

0.237 inches

#### Lubrication:

Cetyl alcohol

#### End Application:

Rq-4-a

### Grip Length:

Between 0.433 inches and 0.443 inches

#### Thready Qty Per Inch (tpi):

32

# Thread Size:

0.164 inches

# Shear Strength:

4010 double pounds per square inch

# **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

# Product Name:

Pin, flush, eddie

# **Special Features:**

Spline-lok recess

# Material:

Titanium alloy uns r56400

# Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

# Thread Series Designator:

Unjc

# Shelf Life:

N/a

# NSN 5320-01-525-6349

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

