NSN 5320-01-525-6746

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-525-6746



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.588 inches and 0.608 inches

Head Style:

Err-090

Head Height:

Between 0.037 inches and 0.047 inches

Width Between Flats:

0.100 inches

Shank Diameter:

Between 0.1630 inches and 0.1635 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.242 inches and 0.262 inches

Lubrication:

Cetyl alcohol

Grip Length:

Between 0.307 inches and 0.317 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.164 inches

Shear Strength:

4010 double pounds per square inch

Product Name:

Pin, protruding, eddie

Special Features:

Spline-lok recess

Material:

Titanium alloy uns r56400

Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

NSN 5320-01-525-6746

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

