## NSN 5320-01-525-6755

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-525-6755 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.650 inches and 0.670 inches **Head Style:** Err-090 **Head Height:** Between 0.037 inches and 0.047 inches Width Between Flats: 0.100 inches **Shank Diameter:** Between 0.1630 inches and 0.1635 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.242 inches and 0.262 inches Lubrication: Cetyl alcohol **End Application:** Rq-4a **Grip Length:** Between 0.370 inches and 0.380 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.164 inches **Shear Strength:** 4010 double pounds per square inch **Product Name:** Pin, protruding, eddie **Special Features:** Spline-lok recess Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Thread Series Designator:** Unjf

Shelf Life:

N/a

## NSN 5320-01-525-6755

Pin-rivet - Page 2 of 2



ı	1	n	iŧ	<b>1</b>	: N/	lea			_	
ı	u	n	IT	OI	١V	ıea	เรเ	JI	е	:

--

Demilitarization:

No

Fiig:

A528u0