# NSN 5320-01-525-6760

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-525-6760



### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.712 inches and 0.732 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.037 inches and 0.047 inches

### Width Between Flats:

0.100 inches

#### Shank Diameter:

Between 0.1630 inches and 0.1635 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.242 inches and 0.262 inches

### Lubrication:

Cetyl alcohol

## **End Application:**

Rq-4a

# Grip Length:

Between 0.433 inches and 0.443 inches

### Thready Qty Per Inch (tpi):

32

## Thread Size:

0.164 inches

# Shear Strength:

4010 double pounds per square inch

### **Product Name:**

Pin, protruding, eddie

#### **Special Features:**

Spline-lok recess

### Material:

Titanium alloy uns r56400

### **Material Specification:**

Ams4928 assn standard single material response or ams4967 assn standard single material response

# Thread Series Designator:

Unjc

# Shelf Life:

N/a

# NSN 5320-01-525-6760

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

