NSN 5320-01-525-6774

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-525-6774 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.482 inches and 0.502 inches **Head Style:** Err-090 **Head Height:** Between 0.045 inches and 0.055 inches Width Between Flats: 0.120 inches **Shank Diameter:** Between 0.1890 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.295 inches and 0.315 inches Lubrication: Cetyl alcohol **End Application:** Rq-4a **Grip Length:** Between 0.183 inches and 0.193 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Shear Strength:** 5380 double pounds per square inch **Product Name:** Pin, protruding, eddie **Special Features:** Spline-lok recess Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Thread Series Designator:** Unjf

N/a

Shelf Life:

NSN 5320-01-525-6774

Pin-rivet - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A528u0