NSN 5320-01-525-6782

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-525-6782 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.552 inches and 0.572 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0801 inches **Shank Diameter:** Between 0.1625 inches and 0.1635 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.2564 inches and 0.2612 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **End Application:** B-2 aircraft **Grip Length:** Between 0.245 inches and 0.255 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.164 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum alloy **Surface Treatment Specification:** Spec. 294, cagec 73197 mfr ref single treatment response **Thread Series Designator:** Unjc

Shelf Life:

N/a

NSN 5320-01-525-6782

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0