

View Online at <https://aerobasegroup.com/nsn/5320-01-525-6791>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.627 inches and 0.647 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.104 inches and 0.119 inches

Shank Diameter:

Between 0.1885 inches and 0.1895 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.2966 inches and 0.3016 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

B-2 aircraft

Grip Length:

Between 0.307 inches and 0.317 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Shear Strength:

95000 single pounds per square inch

Countersink Angle:

100.0 degrees

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Per hi-shear spec. 294 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0