

View Online at <https://aerobasegroup.com/nsn/5320-01-525-7026>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.590 inches and 0.610 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.059 inches and 0.069 inches

**Width Between Flats:**

0.132 inches

**Shank Diameter:**

Between 0.2490 inches and 0.2495 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.387 inches and 0.412 inches

**End Application:**

F/a 22 raptor

**Grip Length:**

Between 0.245 inches and 0.255 inches

**Thready Qty Per Inch (tpi):**

28

**Thread Size:**

0.250 inches

**Shear Strength:**

9300 double pounds per square inch

**Special Features:**

S" indicates spline-lok recess

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams4928 assn standard single material response or ams4967 assn standard single material response

**Surface Treatment:**

Phosphate

**Surface Treatment Specification:**

Ams2486 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0