

View Online at <https://aerobasegroup.com/nsn/5320-01-525-7151>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.885 inches and 0.905 inches

Head Style:

Err-090

Head Height:

Between 0.080 inches and 0.090 inches

Width Between Flats:

Between 0.122 inches and 0.142 inches

Shank Diameter:

Between 0.2485 inches and 0.2495 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.415 inches and 0.440 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

B-2 aircraft

Grip Length:

Between 0.495 inches and 0.505 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.250 inches

Shear Strength:

9300 double pounds per square inch

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Per hi-shear spec.No. 294 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0