

View Online at <https://aerobasegroup.com/nsn/5320-01-525-7151>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.885 inches and 0.905 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.080 inches and 0.090 inches

**Width Between Flats:**

Between 0.122 inches and 0.142 inches

**Shank Diameter:**

Between 0.2485 inches and 0.2495 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.415 inches and 0.440 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**End Application:**

B-2 aircraft

**Grip Length:**

Between 0.495 inches and 0.505 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Size:**

0.250 inches

**Shear Strength:**

9300 double pounds per square inch

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

Per hi-shear spec.No. 294 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0