NSN 5320-01-525-7680

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-525-7680 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.715 inches and 0.735 inches **Head Style:** Err-090 **Head Height:** Between 0.080 inches and 0.090 inches Width Between Flats: 0.160 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.415 inches and 0.440 inches Lubrication: Cetyl alcohol **End Application:** Rq-4a **Grip Length:** Between 0.370 inches and 0.380 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Shear Strength:** 9300 double pounds per square inch **Product Name:** Pin, protruding, eddie **Special Features:** Spline-lok recess Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Thread Series Designator:** Unjf

N/a

Shelf Life:

NSN 5320-01-525-7680

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0