NSN 5320-01-525-7998

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-525-7998



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.650 inches and 0.670 inches

Head Style:

Flush countersunk

Width Between Flats:

0.100 inches

Shank Diameter:

Between 0.1630 inches and 0.1635 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.272 inches and 0.292 inches

Lubrication:

Cetyl alcohol

Grip Length:

Between 0.370 inches and 0.380 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.164 inches

Shear Strength:

4010 double pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Product Name:

Pin, flush, eddie

Special Features:

Spline-lok recess

Material:

Titanium alloy uns r56400

Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

NSN 5320-01-525-7998

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

