NSN 5320-01-525-9403

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-525-9403

Thread Class:

Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 0.715 inches and 0.735 inches
Head Style:
Flush countersunk
Width Between Flats:
0.160 inches
Shank Diameter:
Between 0.2450 inches and 0.2495 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
0.359 inches
Lubrication:
Cetyl alcohol
End Application:
Rq-4a
Grip Length:
Between 0.370 inches and 0.380 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
3700 pounds per square inch
Thread Size:
0.2500 inches
Shear Strength:
9300 double pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Titanium alloy uns r56400
Material Specification:
Ams 4928 assn standard single material response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

NSN 5320-01-525-9403

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0