NSN 5320-01-526-0521

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-526-0521 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.670 inches and 0.690 inches **Head Style:** Flush countersunk Width Between Flats: 0.120 inches **Shank Diameter:** Between 0.1890 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.350 inches Lubrication: Cetyl alcohol **End Application:** Rq-4a **Grip Length:** Between 0.370 inches and 0.380 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 3180 pounds per square inch **Thread Size:** 0.1900 inches **Shear Strength:** 5380 double pounds per square inch **Countersink Angle:** Between 99.30 degrees and 100.30 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response **Thread Series Designator:** Unjf Shelf Life:

Unit Of Measure:

N/a

NSN 5320-01-526-0521

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0