NSN 5320-01-526-1177

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-526-1177 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.755 inches and 0.775 inches **Head Style:** Straight pan **Head Height:** Between 0.080 inches and 0.090 inches Width Between Flats: 0.160 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.415 inches and 0.440 inches Lubrication: Cetyl alcohol **End Application:** Rq-4a **Grip Length:** Between 0.425 inches and 0.435 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 5320 pounds per square inch **Thread Size:** 0.2500 inches **Shear Strength:** 9380 double pounds per square inch Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response **Thread Series Designator:** Unjf Shelf Life:

N/a

Unit Of Measure:

NSN 5320-01-526-1177

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0