NSN 5320-01-526-3005

View Online at https://aerobasegroup.com/nsn/5320-01-526-3005

Pin-rivet - Page 1 of 2

Thread Class:

За



Thread Direction: Right-hand Fastener Length: Between 0.840 inches and 0.860 inches **Head Style:** Flush countersunk **Head Height:** 0.960 inches Width Between Flats: 0.160 inches **Shank Diameter:** Between 0.2450 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.359 inches Lubrication: Cetyl alcohol **End Application:** Rq-4a **Grip Length:** Between 0.495 inches and 0.505 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 3700 pounds per square inch **Thread Size:** 0.2500 inches **Shear Strength:** 9300 double pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a

NSN 5320-01-526-3005

Pin-rivet - Page 2 of 2



ı	1	n	iŧ	1	: N/	lea			_	
ı	u	n	IT	OI	١V	ıea	เรเ	JI	е	:

--

Demilitarization:

No

Fiig:

A528u0