

View Online at <https://aerobasegroup.com/nsn/5320-01-526-3356>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.090 inches and 1.110 inches

Head Style:

Flush countersunk

Head Height:

0.108 inches

Width Between Flats:

0.160 inches

Shank Diameter:

Between 0.2481 inches and 0.2495 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

0.475 inches

Lubrication:

Cetyl alcohol

End Application:

Rq-4a

Grip Length:

Between 0.745 inches and 0.755 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

5820 pounds per square inch

Thread Size:

0.2500 inches

Shear Strength:

9300 double pounds per square inch

Countersink Angle:

Between 99.30 degrees and 100.30 degrees

Material:

Titanium alloy uns r56400

Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

+5103 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

spec.