

View Online at <https://aerobasegroup.com/nsn/5320-01-526-3421>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.637 inches and 0.657 inches

Head Style:

Straight pan

Head Height:

Between 0.080 inches and 0.090 inches

Width Between Flats:

0.160 inches

Shank Diameter:

Between 0.2481 inches and 0.2485 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.415 inches and 0.440 inches

Lubrication:

Cetyl alcohol

End Application:

Rq-4a

Grip Length:

Between 0.307 inches and 0.317 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

5320 pounds per square inch

Thread Size:

0.2500 inches

Shear Strength:

9380 double pounds per square inch

Material:

Titanium alloy uns r56400

Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

+5103 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

spec.