# NSN 5320-01-526-3920

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-526-3920



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 1.177 inches and 1.197 inches

# Head Style:

Cooper's

#### **Head Height:**

Between 0.0388 inches and 0.0408 inches

#### Width Between Flats:

Between 0.0791 inches and 0.0801 inches

#### Shank Diameter:

Between 0.1630 inches and 0.1635 inches

#### Shank Style:

Pin-rivet, straight, threaded

# Head Major Diameter:

0.2612 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corporation and solid film

### **End Application:**

F-18 e/f fighter aircraft

# Grip Length:

1.062 inches

### Thready Qty Per Inch (tpi):

32

# Thread Size:

0.164 inches

# Shear Strength:

95000 single pounds per square inch

#### **Countersink Angle:**

100.0 degrees

### Criticality Code Justification:

Agav

#### **Product Name:**

(inavy)pin-rivet, threaded

### Material:

Titanium alloy uns r56400

# Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

# **Thread Series Designator:**

Unjc

# NSN 5320-01-526-3920

Pin-rivet - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

