
## NSN 5320-01-526-4027

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.990 inches and 1.010 inches

## Head Style:

Straight pan

#### **Head Height:**

Between 0.068 inches and 0.078 inches

#### Width Between Flats:

Between 0.127 inches and 0.129 inches

#### Shank Diameter:

Between 0.311 inches and 0.312 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.475 inches and 0.505 inches

#### Lubrication:

Solid film or dry film and cetyl alcohol

## End Application:

F/a-18 e/f aircraft

## Grip Length:

0.500 inches

#### Thready Qty Per Inch (tpi):

24

#### Thread Size:

0.312 inches

#### Criticality Code Justification:

Agav

#### **Product Name:**

(inavy) pin-rivet, threaded, shear, protruding head, hex point drive, for sealant application

#### Material:

Stainless steel

#### **Material Specification:**

Ams 5629 assn standard single material response

#### Surface Treatment:

Passivate

#### Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

#### **Thread Series Designator:**

Unjf

# NSN 5320-01-526-4027

Pin-rivet - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

