

View Online at <https://aerobasegroup.com/nsn/5320-01-526-4031>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.990 inches and 1.010 inches

Head Style:

Straight pan

Head Height:

Between 0.068 inches and 0.078 inches

Width Between Flats:

Between 0.127 inches and 0.129 inches

Shank Diameter:

Between 0.311 inches and 0.312 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.475 inches and 0.505 inches

Lubrication:

Solid film or dry film and cetyl alcohol

End Application:

F/a-18 e/f aircraft

Grip Length:

0.500 inches

Thready Qty Per Inch (tpi):

24

Thread Size:

0.312 inches

Criticality Code Justification:

Agav

Product Name:

(inavy) pin-rivet, threaded, shear, protruding head, hex point drive, for sealant application

Material:

Stainless steel

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0