

View Online at <https://aerobasegroup.com/nsn/5320-01-526-5344>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.663 inches and 0.683 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.104 inches and 0.119 inches

Shank Diameter:

Between 0.202 inches and 0.203 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

0.332 inches

End Application:

B-2 bomber

Grip Length:

Between 0.308 inches and 0.318 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

95000 pounds per square inch

Thread Size:

0.190 inches

Shear Strength:

6130 double pounds per square inch

Countersink Angle:

130.0 degrees

Material:

Titanium

Material Specification:

Ams4928 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Hi-kote 1 aluminum coating per hi-shear spec0.Hi-kote 1 aluminum coating per hi-shear spec0 294 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0