

View Online at <https://aerobasegroup.com/nsn/5320-01-526-8922>

Thread Class:

3a

Thread Direction:

Right-hand

Head Style:

Countersunk w/reverse chamfer

Head Height:

Between 0.064 inches and 0.074 inches

Shank Diameter:

Between 0.201 inches and 0.202 inches

Shank Style:

Pin-rivet, tapered, threaded

Head Major Diameter:

Between 0.357 inches and 0.377 inches

Tip Diameter:

Between 0.181 inches and 0.184 inches

Collar Outside Diameter:

Between 0.355 inches and 0.365 inches

Collarheight:

Between 0.427 inches and 0.457 inches

Collar Inside Diameter:

0.255 inches

End Application:

Helicopter ch-53g

Features Provided:

Washer

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Shear Strength:

6130 double pounds per square inch

Countersink Angle:

45.0 degrees

Collar Style:

Threaded break off type

Product Name:

Hi-lok fastener

Special Features:

Collar finish cadmium plate per ams-qq-p-416, type i, class 2; grip length in inches 0.750

Material:

Steel body

Material Specification:

Mil-s-5000 military specification single material response body

Surface Treatment:

Cadmium body

Surface Treatment Specification:

Qq-p-416, type i, class 2 federal specification single treatment response body

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.