# NSN 5320-01-526-9810

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-526-9810



# **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 1.802 inches and 1.822 inches

# Head Style:

Straight pan

# **Head Height:**

Between 0.102 inches and 0.112 inches

## Width Between Flats:

Between 0.127 inches and 0.129 inches

#### Shank Diameter:

Between 0.327 inches and 0.328 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.475 inches and 0.505 inches

Lubrication:

Solid film

**End Application:** 

A10

Grip Length:

Between 1.307 inches and 1.317 inches

# Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

12300 pounds per square inch

# Thread Size:

0.312 inches

## Shear Strength:

21100 double pounds per square inch

#### Material:

Steel comp xm-13

## Material Specification:

5629 assn standard all material responses

## **Thread Series Designator:**

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

# NSN 5320-01-526-9810

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

