NSN 5320-01-527-0225

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-527-0225

Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Head Major Diameter:
0.531 inches
Expansion Device:
Threaded stem
Lubrication:
Carbo wax or paraffin wax or cetyl alcohol or dry film
Grip Length:
Between 0.345 inches and 0.405 inches
Features Provided:
Self-locking Self-locking
Hardness Rating:
39.0 rockwell c nut and 46.0 rockwell c nut
Countersink Angle:
100.0 degrees
Product Name:
Visu-lok, fastener, blind internally threaded, external sleeve alloy steel 100 degrees reduced flush head, self locking ground shank, 1/32
inch oversize
Special Features:
Screw material alloy steel; heat treat nut and screw per mil-h-6875 to rc 39-46, sleeve as required for performance
Material:
Stainless steel sleeve
Material Specification:
Qq-5-7635 federal specification 1st material response sleeve or ams 5639 assn standard 2nd material response sleeve or ams 5641 assn
standard 3rd material response sleeve
Surface Treatment:
Passivate sleeve and cadmium sleeve
Surface Treatment Specification:
Qq-p-416, type ii, class 2 federal specification single treatment response nut
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0

Mil-s-6758 spec.

Mil-std (military Standard):