NSN 5320-01-527-0910

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-527-0910 **Thread Class:** За **Identification Code Color:** Blue **Head Style:** Countersunk w/reverse chamfer **Head Height:** Between 0.0785 inches and 0.0805 inches **Shank Diameter:** Between 0.1885 inches and 0.1895 inches

Stump

Shank Style:

Head Major Diameter:

Between 0.3765 inches and 0.3816 inches

Collar Outside Diameter:

0.340 inches

Collarheight:

0.470 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Collar Inside Diameter:

Between 0.192 inches and 0.200 inches

End Application:

Ch-53g-helicopter

Grip Length:

0.375 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.188 inches

Countersink Angle:

100.0 degrees

Collar Style:

Threaded break off type

Material:

Steel comp 4340 body

Material Specification:

Mil-s-5626 military specification all material responses body or mil-s-6049 military specification all material responses body

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, ty ii, cl2 federal specification all treatment responses

NSN 5320-01-527-0910

Pin-rivet - Page 2 of 2



| Thread Series Designator: |
|---------------------------|
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| |
| No |
| No Fiig: |
| |

Mil-std (military Standard):

Mil-s-5626 spec.