## NSN 5320-01-527-0912

Pin-rivet - Page 1 of 2

**Thread Class:** 

3a

View Online at https://aerobasegroup.com/nsn/5320-01-527-0912



## **Identification Code Color:** Blue **Head Style:** Countersunk w/reverse chamfer **Head Height:** Between 0.0785 inches and 0.0805 inches Shank Diameter: Between 0.1885 inches and 0.1895 inches Shank Style: Stump Head Major Diameter: Between 0.3765 inches and 0.3816 inches **Collar Outside Diameter:** 0.340 inches **Collarheight:** 0.470 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Collar Inside Diameter:** Between 0.192 inches and 0.200 inches **End Application:** Ch-53g-helicopter Grip Length: 0.188 inches Thready Qty Per Inch (tpi): 32 Thread Size: 0.188 inches **Countersink Angle:** 100.0 degrees **Collar Style:** Threaded break off type Material: Steel comp 4340 **Material Specification:**

Mil-s-5626 military specification all material responses body or mil-s-6049 military specification all material responses body

Surface Treatment:

Cadmium

**Surface Treatment Specification:** 

Qq-p-416, ty ii, cl2 federal specification all treatment responses

## NSN 5320-01-527-0912

Pin-rivet - Page 2 of 2

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5626 spec.

