
NSN 5320-01-527-1304

Pin-rivet - Page 1 of 2





Thread Class:

3a

Head Style:

Countersunk w/reverse chamfer

Head Height:

Between 0.064 inches and 0.074 inches

Shank Diameter:

Between 0.2016 inches and 0.2026 inches

Shank Style:

Stump

Head Major Diameter:

Between 0.357 inches and 0.377 inches

Collar Outside Diameter:

Between 0.355 inches and 0.365 inches

Collarheight:

Between 0.427 inches and 0.457 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Collar Inside Diameter:

0.255 inches

End Application:

Ch-53g-helicopter

Grip Length:

0.562 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.203 inches

Countersink Angle:

100.0 degrees

Collar Style:

Threaded break off type

Material:

Steel body

Material Specification:

Mil-s-562 military specification single material response body or mil-s-6049 military specification single material response body

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, ty ii, cl2 federal specification all treatment responses body

Thread Series Designator:

Unjf

NSN 5320-01-527-1304

Pin-rivet - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-562 spec.

