# NSN 5320-01-527-1311

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-527-1311



#### **Thread Class:**

3a

## Head Style:

Countersunk w/reverse chamfer

### Head Height:

Between 0.064 inches and 0.074 inches

#### Shank Diameter:

Between 0.2016 inches and 0.2026 inches

#### Shank Style:

Stump

#### Head Major Diameter:

Between 0.357 inches and 0.377 inches

#### **Collar Outside Diameter:**

Between 0.303 inches and 0.307 inches

#### Collarheight:

Between 0.437 inches and 0.457 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

#### Collar Inside Diameter:

Between 0.208 inches and 0.212 inches

#### **End Application:**

Ch-53g-helicopter

### Grip Length:

0.312 inches

#### Thready Qty Per Inch (tpi):

32

#### Thread Size:

0.203 inches

#### **Countersink Angle:**

100.0 degrees

#### **Collar Style:**

Threaded break off type

#### Material:

Steel body

#### Material Specification:

Mil-s-562 military specification single material response body or mil-s-6049 military specification single material response body

#### Surface Treatment:

Cadmium

#### Surface Treatment Specification:

Qq-p-416, ty ii, cl2 federal specification all treatment responses body

#### **Thread Series Designator:**

Unjf

# NSN 5320-01-527-1311

Pin-rivet - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

# Mil-std (military Standard):

Mil-s-562 spec.

