NSN 5320-01-527-1320

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-527-1320 **Thread Class:** За **Head Style:** Countersunk w/reverse chamfer **Head Height:** Between 0.064 inches and 0.074 inches **Shank Diameter:** Between 0.2016 inches and 0.2026 inches **Head Major Diameter:** Between 0.357 inches and 0.377 inches **Collar Outside Diameter:** Between 0.355 inches and 0.365 inches Collarheight: Between 0.427 inches and 0.457 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Collar Inside Diameter:** 0.255 inches **End Application:** Ch-53g-helicopter **Grip Length:** 0.438 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.203 inches **Countersink Angle:**

100.0 degrees

Collar Style:

Threaded break off type

Material:

Steel body

Material Specification:

Mil-s-562 military specification single material response body or mil-s-6049 military specification single material response body

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, ty ii, cl2 federal specification all treatment responses body

Thread Series Designator:

Unjf

Shelf Life:

N/a

NSN 5320-01-527-1320

Pin-rivet - Page 2 of 2



U	n	it	Of	Μe	eas	ur	e:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-562 spec.